


DATA SHEET
PS2F 4000 N25 Thermal Store

	Main Features	
	Application	Storage and subsequent distribution of thermal energy from solid-fuel boilers, heat pumps or other heat sources; the tank is fitted with 2 flanged openings that can permit installation of a DHW tube heat exchanger or connecting a solar thermal system. It is fitted with G 2.5" F threaded tappings.
	Working fluid	water, water-glycol mixture (max. 1:1), water-glycerine mixture (max. 2:1), thermal oil
	Storage tank code	14463
	Insulation code	19356

Energy Efficiency Data (as per EC Regulation No. 812/2013)	
	valid for a tank with insulation
Energy efficiency class	N/A
Static loss	306 W
Storage volume	3996 l

Technical data	
Total storage tank volume	3996 l
Max. working temperature in storage tank	95 °C
Max. working pressure in storage tank	3 bar
Storage tank diameter	1600 mm
Storage tank diameter with insulation	1800 mm
Storage tank overall height	2355 mm
Tipping height without insulation	2490 mm
Storage tank perimeter insulation thickness	100 mm
Storage tank bottom insulation thickness	50 mm
Storage tank top insulation thickness	100 mm
Empty weight without insulation	429 kg

Materials	
Storage tank material	S235JR
Storage tank perimeter insulation	fleece
Storage tank outer surface insulation	hard polystyrene
Top and bottom storage tank insulation	fleece

PS2F 4000 N25 Thermal Store

Accessories	
Electrical heating element	ETT-A, C, D, F, P, M
Heating element max. length	955 mm
Blind flange	code 6230
Blind flange for heat exchanger	code 6231 / 6232
Tube heat exchanger	max. area 4.5 m ²

For the electric heater, a G 2.5" M x G 6/4" F reducer must be used

Dimensions		TAPPINGS																																																																																										
	<table border="1"> <thead> <tr> <th>pos.</th> <th>description</th> <th>connection</th> <th>height [mm]</th> </tr> </thead> <tbody> <tr> <td colspan="4">Heat sources</td> </tr> <tr> <td>B1</td> <td>Supply from heat source</td> <td>G 2.5" F</td> <td>1815</td> </tr> <tr> <td>B2</td> <td>Return to heat source</td> <td>G 2.5" F</td> <td>465</td> </tr> <tr> <td colspan="4">Heating system</td> </tr> <tr> <td>H1</td> <td>Supply to heat sink</td> <td>G 2.5" F</td> <td>2355</td> </tr> <tr> <td>H2</td> <td>Return from heat sink</td> <td>G 2.5" F</td> <td>465</td> </tr> <tr> <td colspan="4">Control and safety</td> </tr> <tr> <td>C1</td> <td>Temperature sensor</td> <td>G 1/2" F</td> <td>1840</td> </tr> <tr> <td>C2</td> <td>Temperature sensor</td> <td>G 1/2" F</td> <td>700</td> </tr> <tr> <td>C3</td> <td>Temperature sensor</td> <td>G 1/2" F</td> <td>1630</td> </tr> <tr> <td>T</td> <td>Thermometer</td> <td>G 1/2" F</td> <td>1490</td> </tr> <tr> <td>P</td> <td>Safety valve</td> <td>G 1/2" F</td> <td>780</td> </tr> <tr> <td colspan="4">Universal inlet/outlet</td> </tr> <tr> <td>U1</td> <td>Universal inlet/outlet</td> <td>G 2.5" F</td> <td>1815</td> </tr> <tr> <td>U2</td> <td>Universal inlet/outlet</td> <td>G 2.5" F</td> <td>675</td> </tr> <tr> <td>U3</td> <td>Universal inlet/outlet</td> <td>G 2.5" F</td> <td>1375</td> </tr> <tr> <td>U4</td> <td>Universal inlet/outlet</td> <td>G 2.5" F</td> <td>905</td> </tr> <tr> <td>U5</td> <td>Universal inlet/outlet</td> <td>G 2.5" F</td> <td>1605</td> </tr> <tr> <td colspan="4">Flanges</td> </tr> <tr> <td>L1</td> <td>Upper flange</td> <td>12 x M12</td> <td>1735</td> </tr> <tr> <td>L2</td> <td>Lower flange</td> <td>12 x M12</td> <td>555</td> </tr> </tbody> </table>					pos.	description	connection	height [mm]	Heat sources				B1	Supply from heat source	G 2.5" F	1815	B2	Return to heat source	G 2.5" F	465	Heating system				H1	Supply to heat sink	G 2.5" F	2355	H2	Return from heat sink	G 2.5" F	465	Control and safety				C1	Temperature sensor	G 1/2" F	1840	C2	Temperature sensor	G 1/2" F	700	C3	Temperature sensor	G 1/2" F	1630	T	Thermometer	G 1/2" F	1490	P	Safety valve	G 1/2" F	780	Universal inlet/outlet				U1	Universal inlet/outlet	G 2.5" F	1815	U2	Universal inlet/outlet	G 2.5" F	675	U3	Universal inlet/outlet	G 2.5" F	1375	U4	Universal inlet/outlet	G 2.5" F	905	U5	Universal inlet/outlet	G 2.5" F	1605	Flanges				L1	Upper flange	12 x M12	1735	L2	Lower flange	12 x M12
pos.	description	connection	height [mm]																																																																																									
Heat sources																																																																																												
B1	Supply from heat source	G 2.5" F	1815																																																																																									
B2	Return to heat source	G 2.5" F	465																																																																																									
Heating system																																																																																												
H1	Supply to heat sink	G 2.5" F	2355																																																																																									
H2	Return from heat sink	G 2.5" F	465																																																																																									
Control and safety																																																																																												
C1	Temperature sensor	G 1/2" F	1840																																																																																									
C2	Temperature sensor	G 1/2" F	700																																																																																									
C3	Temperature sensor	G 1/2" F	1630																																																																																									
T	Thermometer	G 1/2" F	1490																																																																																									
P	Safety valve	G 1/2" F	780																																																																																									
Universal inlet/outlet																																																																																												
U1	Universal inlet/outlet	G 2.5" F	1815																																																																																									
U2	Universal inlet/outlet	G 2.5" F	675																																																																																									
U3	Universal inlet/outlet	G 2.5" F	1375																																																																																									
U4	Universal inlet/outlet	G 2.5" F	905																																																																																									
U5	Universal inlet/outlet	G 2.5" F	1605																																																																																									
Flanges																																																																																												
L1	Upper flange	12 x M12	1735																																																																																									
L2	Lower flange	12 x M12	555																																																																																									