

DATA SHEET

CSE2 MIX F W6 1F Pump Station




Main Features

Application	It provides flow through the heating system, mixes to the outlet temperature in an electric actuated mixing valve (controlled by an external controller). The pump station includes a filter with magnet, so it is also suitable for older steel pipe systems. It can be easily mounted on a wall or on a manifold for multiple heating circuits.
Description	Consists of RPA 25-8 pump, LK 840 3-way mixing valve with AVC actuator, filter w. magnet, check valve, ball valves w. sensor sheaths, insulation.
Working fluid	Water, water-glycol mixture (max. 1:1). pH range 6.5–8.5.
Installation	Vertically on a wall or manifold (125 mm pitch).
Code	21126


Pump Station Data

Fluid working temperature	5–95 °C
Max. working pressure	10 bar
Min. working pressure	0.5 bar
Ambient temperature	5–40 °C
Max. relative humidity	80 %, non condensing
Pump station max. power input	67 W
Pump power supply	230 V, 50 Hz
Max. current to pump	0.65 A
Mixing valve actuator torque	5 Nm
Angle of the mixing valve actuator	90°
Mixing valve shift time	120 s
Power supply and control of the mixing	230 V, 50 Hz; from external controller w. 3-point control
Mixing valve Kvs	6.3 m³/h
Max. pressure difference	5 mH ₂ O (at mixing valve inlets)
Leak rate	< 1 % Kvs at 5 mH ₂ O pressure difference (at mixing valve inlets)
Insulation material	EPP RG 60 g/l
Overall dimensions	360 x 181 x 245 mm
Total weight	6.7 kg
Connections	4 x G 1" F

Pump Station Pressure Drop



Example of possible connection




The diagram shows a typical connection of a solid fuel boiler (with the recommended RGMAT pump station – not included in supply), combination thermal store and heating circuit.

DATA SHEET


CSE2 MIX F R8 1F Pump Station

Pump Performance Curves

Constant speed



Variable pressure



Constant pressure

